

Caddy auf Hetzner

Installation:

```
ssh hetzner

apt install -y debian-keyring debian-archive-keyring apt-transport-https curl
curl -1sLf 'https://dl.cloudsmith.io/public/caddy/stable/gpg.key' | gpg --dearmor -o
/usr/share/keyrings/caddy-stable-archive-keyring.gpg
curl -1sLf 'https://dl.cloudsmith.io/public/caddy/stable/debian.deb.txt' | tee
/etc/apt/sources.list.d/caddy-stable.list
apt update
apt install -y caddy
```

Caddyfile:

```
nano /etc/caddy/Caddyfile
```

Inhalt:

```
enode.eu {
    basicauth {
        denode $2a$14$<BCRYPT_HASH>
    }

    root * /var/www/denode
    file_server
    encode gzip
}

nextcloud.denode.eu {
    encode gzip
    reverse_proxy 10.100.0.2:80 {
        header_up Host {host}
        header_up X-Real-IP {remote_host}
        header_up X-Forwarded-For {remote_host}
        header_up X-Forwarded-Proto {scheme}
    }
}
```

```
}

notes.denode.eu {
    basicauth {
        denode $2a$14$<BCRYPT_HASH>
    }

    encode gzip

    reverse_proxy 10.100.0.2:4567 {
        header_up Host {host}
        header_up X-Real-IP {remote_host}
        header_up X-Forwarded-For {remote_host}
        header_up X-Forwarded-Proto {scheme}
    }
}

overleaf.denode.eu {
    basicauth {
        denode $2a$14$<BCRYPT_HASH>
    }

    encode gzip

    reverse_proxy 10.100.0.2:4568 {
        header_up Host {host}
        header_up X-Real-IP {remote_host}
        header_up X-Forwarded-For {remote_host}
        header_up X-Forwarded-Proto {scheme}
    }
}
```

Passwort hashen

```
caddy hash-password
```

Caddy reload

```
systemctl reload caddy
systemctl status caddy
```

Revision #1

Created 2025-12-06 12:17:52 UTC by Denode

Updated 2025-12-06 12:17:52 UTC by Denode