

Caddy auf Homesever

Caddyfile

```
sudo nano /etc/caddy/Caddyfile
```

Inhalt:

```
enode.eu {
    basicauth {
        denode $2a$14$<BCRYPT_HASH>
    }

    root * /var/www/denode
    file_server
    encode gzip
}

nextcloud.denode.eu {
    encode gzip
    reverse_proxy 10.100.0.2:80 {
        header_up Host {host}
        header_up X-Real-IP {remote_host}
        header_up X-Forwarded-For {remote_host}
        header_up X-Forwarded-Proto {scheme}
    }
}

notes.denode.eu {
    basicauth {
        denode $2a$14$<BCRYPT_HASH>
    }

    encode gzip
    reverse_proxy 10.100.0.2:4567 {
        header_up Host {host}
        header_up X-Real-IP {remote_host}
    }
}
```

```
        header_up X-Forwarded-For {remote_host}
        header_up X-Forwarded-Proto {scheme}
    }
}

overleaf.denode.eu {
    basicauth {
        denode $2a$14$<BCRYPT_HASH>
    }

    encode gzip
    reverse_proxy 10.100.0.2:4568 {
        header_up Host {host}
        header_up X-Real-IP {remote_host}
        header_up X-Forwarded-For {remote_host}
        header_up X-Forwarded-Proto {scheme}
    }
}
```

Caddy reload

```
sudo systemctl reload caddy
sudo systemctl status caddy
```

Revision #1

Created 2025-12-06 12:17:52 UTC by Denode

Updated 2025-12-06 12:17:52 UTC by Denode